



CE LVD TEST REPORT

For
SOLAR LED STREETLIGHT

Model No.: VT-ST-100W, VT-ST-150W, VT-ST-200W, VT-ST-300W, VT-ST15, VT-ST21, VT-ST41, VT-ST61

Applicant : V-TAC EXPORTS LIMITED
ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD
CENTRAL, CENTRAL, HONGKONG

Manufacturer : V-TAC EXPORTS LIMITED
ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD
CENTRAL, CENTRAL, HONGKONG

Issued By : Global-Standard Testing Service Co., Ltd.
Room 1505 Building B, Chuangxin Plaza, Pingshan Avenue,
Pingshan District, Shenzhen, China

Tel : +86 755 33863599 *

Email : market@gstslab.com

Report Number : GST.190823.A101S

Issued Date : September 26, 2019

Date of Report : September 26, 2019

Note:

1. The test data and result is based on the tested sample.
2. Please verify information in the report on GST web: www.gstslab.com by using report number. Or email to us..
3. All rights reserve, the pirate edition investigates necessarily! This report shall not be reproduced unless under the authority of Global-Standard Testing Service Co., Ltd.

LVD Report EN60598-1&EN60598-2-5 Luminaires—Part 1 :General requirements and tests Part 2: Particular requirements Section Three – Luminaires for road and street lighting	
Report reference No.:	GST.190823.A101S
Testing laboratory	Global-Standard Testing Service Co., Ltd.
Location.....:	Room 1505, Building B, Chuangxin Plaza, Pingshan Avenue, Pingshan District, Shenzhen, China.
Applicant.....:	V-TAC EXPORTS LIMITED
Address.....:	ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD CENTRAL, CENTRAL, HONGKONG
Manufacturer.....:	V-TAC EXPORTS LIMITED
Address.....:	ROOM NO.301, KAM ON BUILDING 176A QUEENS ROAD CENTRAL, CENTRAL, HONGKONG
Standards.....:	EN 60598-1:2015+A1:2018 EN 60598-2-5: 2015 EN 62031:2008+A1:2013+A2:2015 EN 62471:2008 EN 62493:2015
Procedure deviation.....:	N/A
Non-standard test method.....:	N/A
Type of test equipment	SOLAR LED STREETLIGHT
Trade mark.....:	NA
Model/Type designation.....:	VT-ST-100W, VT-ST-150W, VT-ST-200W, VT-ST-300W, VT-ST15, VT-ST21, VT-ST41, VT-ST61
Rating.....:	6.4V, Max.300W
TRF originator.....:	Global-Standard Testing Service Co., Ltd.
Copyright blank test report.....:	Global-Standard Testing Service Co., Ltd.
Test item particulars.....:	--
Operating Condition.....:	Continuous
Tested for IT power systems.....:	No
IT testing, phase-phase voltage (V)....:	N/A.
Class of equipment.....:	Class III equipment and Fixed equipment
Protection against ingress of water	IP65

Possible test case verdicts :	
test case does not apply to the test object	N(/A.)
test object does meet the requirement	P(ass)
test object does not meet the requirement	F(ail)

Name and address of the testing laboratory :

Global-Standard Testing Service Co., Ltd.
Room 1505, Building B, Chuangxin Plaza, Pingshan Avenue,
Pingshan District, Shenzhen, China

Tested by : John Huang September 22, 2019
Signature Date

John Huang / Engineer
Name/title

Reviewed by : Gloria Wang September 26, 2019
Signature Date


Gloria Wang / Project engineer
Name/title

Approved by : Nico Xie September 26, 2019
Signature Date

Nico Xie / Manager
Name/title

General remarks:	
<p>Clause number between brackets refer to clauses in IEC 60598-1</p> <p>"(see remark #)" refers to a remark appended to the report.</p> <p>"(see appended table)" refers to a table appended to the report.</p> <p>Throughout this report a comma is used as the decimal separator.</p> <p>The test results presented in this report relate only to the object tested.</p> <p>This report shall not be reproduced except in full without the written approval of the testing laboratory.</p> <p>Unless otherwise specified, test are made under normal conditions at an ambient temperature within the range of 15°C to 35°C, RH45% to 75% and an air pressure of 860mbar of 1060mbar</p>	<p>Attachment with:</p> <p>1) Photo documentation</p>
<p>Brief description of the test sample:</p> <p>1.This report covers the SOLAR LED STREETLIGHT with models VT-ST-100W, VT-ST-150W, VT-ST-200W, VT-ST-300W, VT-ST15, VT-ST21, VT-ST41, VT-ST61.</p> <p>2.All models have the same construction except for appearance, size and wattage.</p> <p>3.The model VT-ST-100W was selected representative sample.</p> <p>4.The safety specifications of LED modules for general lighting was evaluated with reference to EN 62031.</p> <p>5.The standard of EN 62471 and EN 62493 have been considered in report.</p>	

Label



Note:

1. Due to similarity of the labels, only above label was listed.
2. All models have the same marking plate except the model name and input rating with wattage.
3. Height of CE marking at least 5mm, height of WEEE mark at least 7mm, height of other marks at least 5mm, height of letters and numerals at least 2mm.

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
5.4 (0+2)	CLASSIFICATION OF LUMINAIRES		P
5.4 (0.1)	Information for luminaire design considered.....:	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Lamp standard:	—
5.4 (0.3)	More sections applicable.....:	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Section/s:	—
5.4 (2.2)	Type of protection	Class	P
5.4 (2.3)	Degree of protection.....:	IP65	P
5.4 (2.4)	Luminaire suitable for direct mounting on normally flammable surfaces.....:	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	—
5.4 (2.5)	Luminaire for normal use	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	—
	Luminaire for rough service	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	—

5.5 (3)	MARKING		P
5.5 (3.2)	Mandatory markings		P
	Position of the marking		P
	Format of symbols/text		P
5.5 (3.3)	Additional information		P
	Language of instructions	English	P
5.5 (3.3.1)	Combination luminaires		N/A
5.5 (3.3.2)	Nominal frequency in Hz	50/60	P
5.5 (3.3.3)	Operating temperature		N/A
5.5 (3.3.4)	Symbol or warning notice		N/A
5.5 (3.3.5)	Wiring diagram		N/A
5.5 (3.3.6)	Special conditions		N/A
5.5 (3.3.7)	Metal halide lamp luminaire – warning		N/A
5.5 (3.3.8)	Limitation for semi-luminaires		N/A
5.5 (3.3.9)	Power factor and supply current		N/A
5.5 (3.3.10)	Suitability for use indoors		N/A
5.5 (3.3.11)	Luminaires with remote control		N/A
5.5 (3.3.12)	Clip-mounted luminaire – warning		N/A
5.5 (3.3.13)	Specifications of protective shields		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
5.5 (3.3.14)	Symbol for nature of supply		P
5.5 (3.3.15)	Rated current of socket outlet		N/A
5.5 (3.3.16)	Rough service luminaire		N/A
5.5 (3.3.17)	Mounting instruction for type Y, type Z and some type X attachments		P
5.5 (3.3.18)	Non-ordinary luminaires with PVC cable		N/A
5.5 (3.3.19)	Protective conductor current in instruction if applicable		N/A
5.5 (3.3.20)	Provided with information if not intended to be mounted within arm's reach		N/A
5.5 (3.3.21)	Non replaceable and non-user replaceable light sources information provided		P
	Cautionary symbol		P
5.5 (3.3.22)	Controllable luminaires, classification of insulation provided		N/A
5.5 (3.4)	Test with water		P
	Test with hexane		P
	Legible after test		P
	Label attached		P
5.5 (-)	Additional information if applicable		
	a) Operation position		
	b) Weight and dimensions		
	c) Maximum protected area		
	d) Limitation of use indoors and/or outdoor		
	e) Maximum mounting height if ≤ 5 m		

5.6 (4)	CONSTRUCTION		P
5.6 (4.2)	Components replaceable without difficulty		N/A
5.6 (4.3)	Wireways smooth and free from sharp edges		P
5.6 (4.4)	Lampholders		N/A
5.6 (4.4.1)	Integral lampholder		N/A
5.6 (4.4.2)	Wiring connection		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
5.6 (4.4.3)	Lampholder for end- to- end mounting		N/A
5.6 (4.4.4)	Positioning		N/A
	- pressure test (N)		—
	After test the lampholder comply with relevant standard sheets and show no damage		N/A
	After test on single-capped lampholder the lampholder have not moved from its position and show no permanent deformation		N/A
	- bending test (N)		—
	After test the lampholder have not moved from its position and show no permanent deformation		N/A
5.6 (4.4.5)	Peak pulse voltage		N/A
5.6 (4.4.6)	Centre contact		N/A
5.6 (4.4.7)	Parts in rough service luminaires resistant to tracking		N/A
5.6 (4.4.8)	Lamp connectors		N/A
5.6 (4.4.9)	Caps and bases correctly used		N/A
5.6 (4.4.10)	Light source for lampholder or connection according IEC 60061 not connected another way		N/A
5.6 (4.5)	Starter holders		N/A
	Starter holder in luminaires other than class II		N/A
	Starter holder class II construction		N/A
5.6 (4.6)	Terminal blocks		N/A
	Tails		N/A
	Unsecured blocks		N/A
5.6 (4.7)	Terminals and supply connections		P
5.6 (4.7.1)	Contact to metal parts		P
5.6 (4.7.2)	Test 8 mm live conductor		N/A
	Test 8 mm earth conductor		N/A
5.6 (4.7.3)	Terminals for supply conductors		N/A
5.6 (4.7.3.1)	Welded method and material		N/A
	- stranded or solid conductor		N/A
	- spot welding		N/A
	- welding between wires		N/A
	- Type Z attachment		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	- mechanical test according to 15.6.2		N/A
	- electrical test according to 15.6.3		N/A
	- heat test according to 15.6.2.3 and 15.6.2.4		N/A
5.6 (4.7.4)	Terminals other than supply connection		P
5.6 (4.7.5)	Heat-resistant wiring/sleeves		N/A
5.6 (4.7.6)	Multi-pole plug		N/A
	- test at 30 N		N/A
5.6 (4.8)	Switches		N/A
	- adequate rating		N/A
	- adequate fixing		N/A
	- polarized supply		N/A
	- compliance with IEC 61058-1 for electronic switches		N/A
5.6 (4.9)	Insulating lining and sleeves		N/A
5.6 (4.9.1)	Retainment		P
	Method of fixing.....:		P
5.6 (4.9.2)	Insulated linings and sleeves:		N/A
	Resistant to a temperature > 20 °C to the wire temperature or		P
	a) & c) Insulation resistance and electric strength		N/A
	b) Ageing test. Temperature (°C).....:		P
5.6 (4.10)	Double or reinforced insulation		P
5.6 (4.10.1)	No contact, mounting surface – accessible metal parts – wiring of basic insulation		P
	Safe installation fixed luminaires		N/A
	Capacitors and switches		N/A
	Interference suppression capacitors according to IEC 60384-14		N/A
5.6 (4.10.2)	Assembly gaps:		P
	- not coincidental		P
	- no straight access with test probe		P
5.6 (4.10.3)	Retainment of insulation:		P
	- fixed		P

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	- unable to be replaced; luminaire inoperative		P
	- sleeves retained in position		P
	- lining in lampholder		N/A
5.6 (4.10.4)	Protective impedance device		N/A
	Double or reinforced insulation bridged by appropriate and at least two resistors or two Y2 capacitors or one Y1 capacitor		N/A
	Y1 or Y2 capacitors comply with IEC 60384-14		N/A
	Resistors comply with test (a) in 14.1 of IEC 60065		N/A
5.6 (4.11)	Electrical connections and current-carrying parts		P
5.6 (4.11.1)	Contact pressure		P
5.6 (4.11.2)	Screws:		P
	- self-tapping screws	Fixed enclosure and LED PCB	P
	- thread-cutting screws		N/A
5.6 (4.11.3)	Screw locking:		N/A
	- spring washer		N/A
	- rivets		N/A
5.6 (4.11.4)	Material of current-carrying parts		P
5.6 (4.11.5)	No contact to wood or mounting surface		P
5.6 (4.11.6)	Electro-mechanical contact systems		N/A
5.6 (4.12)	Screws and connections (mechanical) and glands		P
5.6 (4.12.1)	Screws not made of soft metal		P
	Screws of insulating material		P
	Torque test: torque (Nm); part.....:		P
	Torque test: torque (Nm); part.....:		N/A
	Torque test: torque (Nm); part.....:		N/A
5.6 (4.12.2)	Screws with diameter < 3 mm screwed into metal		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
5.6 (4.12.4)	Locked connections:		N/A
	- fixed arms; torque (Nm)..... :		N/A
	- lampholder; torque (Nm)..... :		N/A
	- push-button switches; torque 0,8 Nm..... :		N/A
5.6 (4.12.5)	Screwed glands; force (Nm)..... :		N/A
5.6 (4.13)	Mechanical strength		P
5.6 (4.13.1)	Impact tests:		P
	- fragile parts; energy (Nm)..... :		N/A
	- other parts; energy (Nm)..... :		P
	1) live parts		P
	2) linings		P
	3) protection		P
	4) covers		P
5.6 (4.13.3)	Straight test finger		P
5.6 (4.13.4)	Rough service luminaires		N/A
	- IP54 or higher		N/A
	a) fixed		N/A
	b) hand-held		N/A
	c) delivered with a stand		N/A
	d) for temporary installations and suitable for mounting on a stand		N/A
5.6 (4.13.6)	Tumbling barrel		P
5.6 (4.14)	Suspensions, fixings and means of adjusting		P
5.6 (4.14.1)	Mechanical load:		P
	A) four times the weight	Max.2.13Kg	P
	B) torque 2,5 Nm		P
	C) bracket arm; bending moment (Nm)..... :		N/A
	D) load track- mounted luminaires		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	E) clip-mounted luminaires, glass-shelve. Thickness (mm)		N/A
	Metal rod. diameter (mm)		N/A
	Fixed luminaire or independent control gear without fixing devices		N/A
5.6 (4.14.2)	Load to flexible cables		N/A
	Mass (kg)		—
	Stress in conductors (N/mm ²)		N/A
	Mass (kg) of semi-luminaire		N/A
	Bending moment (Nm) of semi-luminaire		N/A
5.6 (4.14.3)	Adjusting devices:		N/A
	- flexing test; number of cycles.....		N/A
	- strands broken.....		N/A
	- electric strength test afterwards		P
5.6 (4.14.4)	Telescopic tubes: cords not fixed to tube; no strain on conductors		P
5.6 (4.14.5)	Guide pulleys		N/A
5.6 (4.14.6)	Strain on socket-outlets		N/A
5.6 (4.15)	Flammable materials		N/A
	- glow-wire test 650°C.....	See Test Table 5.15 (13.3.2)	N/A
	- spacing ≥30 mm		N/A
	- screen withstanding test of 13.3.1		N/A
	- screen dimensions		N/A
	- no fiercely burning material		N/A
	- thermal protection		N/A
	- electronic circuits exempted		N/A
5.6 (4.15.2)	Luminaires made of thermoplastic material with lamp control gear		N/A
	a) construction		N/A
	b) temperature sensing control		N/A
	c) surface temperature		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
5.6 (4.16)	Luminaires for mounting on normally flammable surfaces		P
	No lamp control gear.....:	(compliance with Section 12)	P
5.6 (4.16.1)	Lamp control gear spacing:		N/A
	- spacing 35 mm		N/A
	- spacing 10 mm		N/A
5.6 (4.16.2)	Thermal protection:		N/A
	- in lamp control gear		N/A
	- external		N/A
	- fixed position		N/A
	- temperature marked lamp control gear		N/A
5.6 (4.16.3)	Design to satisfy the test of 12.6	(see clause 12.6)	N/A
5.6 (4.17)	Drain holes		N/A
	Clearance at least 5 mm		N/A
5.6 (4.18)	Resistance to corrosion		P
5.6 (4.18.1)	- rust-resistance		P
5.6 (4.18.2)	- season cracking in copper		N/A
5.6 (4.18.3)	- corrosion of aluminium		N/A
5.6 (4.19)	Ignitors compatible with ballast		N/A
5.6 (4.20)	Rough service vibration		N/A
5.6 (4.21)	Protective shield		N/A
5.6 (4.21.1)	Shield fitted if tungsten halogen lamps or metal halide lamps		N/A
	Shield of glass if tungsten halogen lamps		N/A
5.6 (4.21.2)	Particles from a shattering lamp not impair safety		N/A
5.6 (4.21.3)	No direct path		N/A
5.6 (4.21.4)	Impact test on shield		N/A
	Glow-wire test on lamp compartment.....:	See Test Table 5.15 (13.3.2)	N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
5.6 (4.22)	Attachments to lamps not cause overheating or damage		N/A
5.6 (4.23)	Semi-luminaires comply Class II		N/A
5.6 (4.24)	Photobiological hazards		N/A
5.6 (4.24.1)	No excessive UV radiation if tungsten halogen lamps and metal halide lamps (Annex P)		N/A
5.6 (4.24.2)	Retinal blue light hazard		N/A
	Class of risk group assessed according to IEC/TR 62778		—
	Luminaires with E_{thr} :		N/A
	a) Fixed luminaires		N/A
	- distance x m, borderline between RG1 and RG2... :		N/A
	- marking and instruction according 3.2.23		N/A
	b) Portable and handheld luminaires		N/A
	- marking according 3.2.23 if RG1 exceeded at 200 mm according to IEC/TR 62778		N/A
	Portable luminaires for children IEC 60598-2-10 and Mains socket outlet nightlights IEC 60598-2-12 not exceed RG1 at 200 mm according to IEC/62778		N/A
5.6 (4.25)	Mechanical hazard		P
	No sharp point or edges		P
5.6 (4.26)	Short-circuit protection		N/A
5.6 (4.26.1)	Adequate means of uninsulated accessible SELV parts		N/A
5.6 (4.26.2)	Short-circuit test with test chain according 4.26.3		N/A
	Test chain not melt through		N/A
	Test sample not exceed values of Table 12.1 and 12.2		N/A
5.6 (4.27)	Terminal blocks with integrated screwless earthing contacts		P
	Test according Annex V		N/A
	Pull test of terminal fixing (20 N)		P
	After test, resistance < 0,05 Ω		P
	Pull test of mechanical connection (50 N)		N/A
	After test, resistance < 0,05 Ω		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	Voltage drop test, resistance < 0,05 Ω		P
5.6 (4.28)	Fixing of thermal sensing control		N/A
	Not plug-in or easily replaceable type		N/A
	Reliably kept in position		N/A
	No adhesive fixing if UV radiations from a lamp can degrade the fixing		N/A
	Not outside the luminaire enclosure		N/A
	Test of adhesive fixing:		N/A
	Max. temperature on adhesive material (°C) :		—
	100 cycles between t min and t max		N/A
	Temperature sensing control still in position		N/A
5.6 (4.29)	Luminaires with non-replaceable light source		P
	Not possible to replace light source		P
	Live part not accessible after parts have been opened by hand or tools		P
5.6 (4.30)	Luminaires with non-user replaceable light source		N/A
	If protective cover provide protection against electric shock and marked with “caution, electric shock risk” symbol:		N/A
	Minimum two fixing means		N/A
5.6 (4.31)	Insulation between circuits		P
	Circuits insulated from LV supply fulfil requirements according 4.31.1 – 4.31.3		P
	Controllable luminaires requiring same level of insulation for all components, the insulation between control terminals and LV supply fulfil requirements according 4.31.1 – 4.31.3		P
5.6 (4.31.1)	SELV circuits		P
	Used SELV source		P
	Voltage ≤ ELV		P
	Insulating of SELV circuits from LV supply		N/A
	Insulating of SELV circuits from other non SELV circuits		N/A
	Insulating of SELV circuits from FELV		N/A
	Insulating of SELV circuits from other SELV circuits		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	SELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to enter socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Plugs and socket-outlets does not have protective conductor contact		N/A
5.6 (4.31.2)	FELV circuits		N/A
	Used FELV source		N/A
	Voltage \leq ELV		N/A
	Insulating of FELV circuits from LV supply		N/A
	FELV circuits insulated from accessible parts according Table X.1		N/A
	Plugs not able to enter socket-outlets of other voltage systems		N/A
	Socket outlets does not admit plugs of other voltage systems		N/A
	Socket-outlets does not have protective conductor contact		N/A
5.6 (4.31.3)	Other circuits		N/A
	Other circuits insulated from accessible parts according Table X.1		N/A
	Class II construction with equipotential bonding for protection against indirect contacts with live parts:		N/A
	- conductive parts are connected together		N/A
	- test according 7.2.3		N/A
	- conductive part not cause an electric shock in case of an insulation fault		N/A
	- equipotential bonding in master/slave applications		N/A
	- master luminaire provided with terminal for accessible conductive parts of slave luminaires		N/A
	- slave luminaire constructed as class I		N/A
5.6 (4.32)	Overvoltage protective devices		N/A
	Comply with IEC 61643-11		N/A
	External to controlgear and connected to earth:		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	- only in fixed luminaires		N/A
	- only connected to protective earth		N/A
5.6.1 (-)	At least IPX3 if for outdoor use		P
5.6.2 (-)	Lampholder brackets and lamp supports		P
5.6.3 (-)	Adjusting means		P
5.6.4 (-)	Controlling components		P
5.6.5 (-)	Fixing device		P
	Wind force test		P
5.6.6 (-)	Locking of angular adjustment		P
5.6.7 (-)	Vibration resistance		P
5.6.8 (-)	Requirement on glass cover if mounting height > 5 m		P
	Method of protection		—

5.7 (11)	CREEPAGE DISTANCES AND CLEARANCES		P
5.7 (11.2)	Creepage distances and clearances.....:	See Table 5.7 (11.2)	P
	Impulse withstand category (Normal category II) (Category III Annex U, Table U.1)	Category II <input type="checkbox"/> Category III <input checked="" type="checkbox"/>	—

5.8 (7)	PROVISION FOR EARTHING		P
5.8 (7.2.1 + 7.2.3)	Accessible metal parts		P
	Metal parts in contact with supporting surface		P
	Resistance < 0,5 Ω:		P
	Self-tapping screws used		N/A
	Thread-forming screws		P
	Thread-forming screw used in a grove		N/A
	Earth makes contact first		N/A
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
	Protective earthing of the luminaire not via built-in control gear		N/A
5.8 (7.2.2 + 7.2.3)	Earth continuity in joints, etc.		N/A
5.8 (7.2.4)	Locking of clamping means		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	Compliance with 4.7.3		N/A
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N/A
5.8 (7.2.5)	Earth terminal integral part of connector socket		N/A
5.8 (7.2.6)	Earth terminal adjacent to mains terminals		N/A
5.8 (7.2.7)	Electrolytic corrosion of the earth terminal		P
5.8 (7.2.8)	Material of earth terminal		P
	Contact surface bare metal		P
5.8 (7.2.10)	Class II luminaire for looping-in		N/A
	Double or reinforced insulation to functional earth		N/A
5.8 (7.2.11)	Earthing core coloured green-yellow		P
	Length of earth conductor		P

5.9 (14)	SCREW TERMINALS		N/A
	Separately approved; component list	(see Annex 1)	N/A
	Part of the luminaire	(see Annex 3)	N/A

5.9 (15)	SCREWLESS TERMINALS AND ELECTRICAL CONNECTIONS		N/A
	Separately approved; component list.....:	(see Annex 1)	N/A
	Part of the luminaire.....:	(see Annex 4)	N/A

5.10 (5)	EXTERNAL AND INTERNAL WIRING		P
5.10 (5.2)	Supply connection and external wiring		P
5.10 (5.2.1)	Means of connection.....:		N/A
	Outdoor luminaire has not PVC insulated external wiring if not class III or SELV ≤ 25 V a.c./60 V d.c. or protected from outdoor environment		N/A
5.10 (5.2.2)	Type of cable.....:	24AWG	P
	Nominal cross-sectional area (mm ²).....:	2 X 0.75	P
	Cables equal to IEC 60227 or IEC 60245		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
5.10 (5.2.3)	Type of attachment, X, Y or Z		P
5.10 (5.2.5)	Type Z not connected to screws		N/A
5.10 (5.2.6)	Cable entries:		N/A
	- suitable for introduction		N/A
	- adequate degree of protection		N/A
5.10 (5.2.7)	Cable entries through rigid material have rounded edges		N/A
5.10 (5.2.8)	Insulating bushings:		N/A
	- suitably fixed		N/A
	- material in bushings		N/A
	- material not likely to deteriorate		N/A
	- tubes or guards made of insulating material		N/A
5.10 (5.2.9)	Locking of screwed bushings		N/A
5.10 (5.2.10)	Cord anchorage:		N/A
	- covering protected from abrasion		N/A
	- clear how to be effective		N/A
	- no mechanical or thermal stress		N/A
	- no tying of cables into knots etc.		N/A
	- insulating material or lining		N/A
5.10 (5.2.10.1)	Cord anchorage for type X attachment:		N/A
	a) at least one part fixed		N/A
	b) types of cable		N/A
	c) no damaging of the cable		N/A
	d) whole cable can be mounted		N/A
	e) no touching of clamping screws		N/A
	f) metal screw not directly on cable		N/A
	g) replacement without special tool		N/A
	Glands not used as anchorage		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	Labyrinth type anchorages		N/A
5.10 (5.2.10.2)	Adequate cord anchorage for type Y and type Z attachment		N/A
5.10 (5.2.10.3)	Tests:		N/A
	- impossible to push cable; unsafe		N/A
	- pull test: 25 times; pull (N)..... :		N/A
	- torque test: torque (Nm)..... :		N/A
	- displacement ≤ 2 mm		N/A
	- no movement of conductors		N/A
	- no damage of cable or cord		N/A
	- function independent of electrical connection		N/A
5.10 (5.2.11)	External wiring passing into luminaire		N/A
5.10 (5.2.12)	Looping-in terminals		N/A
5.10 (5.2.13)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		P
5.10 (5.2.14)	Mains plug same protection		N/A
	Class III luminaire plug		N/A
	No unsafe compatibility		N/A
5.10 (5.2.16)	Appliance inlets (IEC 60320)		N/A
	Installation couplers (IEC 61535)		N/A
	Other appliance inlet or connector according relevant IEC standard		N/A
5.10 (5.2.17)	No standardized interconnecting cables properly assembled		N/A
5.10 (5.2.18)	Used plug in accordance with		N/A
	- IEC 60083		N/A
	- other standard		N/A
5.10 (5.3)	Internal wiring		P

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
5.10 (5.3.1)	Internal wiring of suitable size and type		P
	Through wiring		P
	- not delivered/ mounting instruction		P
	- factory assembled		P
	- socket outlet loaded (A)..... :		P
	- temperatures..... :	(see Annex 2)	P
	Green- yellow for earth only		N/A
5.10 (5.3.1.1)	Internal wiring connected directly to fixed wiring		P
	Cross-sectional area (mm ²)..... :		P
	Insulation thickness		P
	Extra insulation added where necessary		P
5.10 (5.3.1.2)	Internal wiring connected to fixed wiring via internal current-limiting device		N/A
	Adequate cross-sectional area and insulation thickness		N/A
5.10 (5.3.1.3)	Double or reinforced insulation for class II		N/A
5.10 (5.3.1.4)	Conductors without insulation		P
5.10 (5.3.1.5)	SELV current-carrying parts		P
5.10 (5.3.1.6)	Insulation thickness other than PVC or rubber		P
5.10 (5.3.2)	Sharp edges etc.		P
	No moving parts of switches etc.		P
	Joints, raising/lowering devices		N/A
	Telescopic tubes etc.		N/A
	No twisting over 360°		N/A
5.10 (5.3.3)	Insulating bushings:		P
	- suitable fixed		P
	- material in bushings		P
	- material not likely to deteriorate		P

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	- cables with protective sheath		N/A
5.10 (5.3.4)	Joints and junctions effectively insulated		N/A
5.10 (5.3.5)	Strain on internal wiring		N/A
5.10 (5.3.6)	Wire carriers		N/A
5.10 (5.3.7)	Wire ends not tinned		N/A
	Wire ends tinned: no cold flow		P

5.11 (8)	PROTECTION AGAINST ELECTRIC SHOCK		P
5.11 (8.2.1)	Live parts not accessible		P
	Basic insulated parts not used on the outer surface without appropriate protection		N/A
	Basic insulated parts not accessible with standard test finger on portable, settable and adjustable luminaires		N/A
	Basic insulated parts not accessible with Ø 50 mm probe from outside, other types of luminaires		N/A
	Lamp and starterholders in portable and adjustable luminaires comply with double or reinforced insulation requirements		N/A
	Basic insulation only accessible under lamp or starter replacement		N/A
	Protection in any position		P
	Double-ended tungsten filament lamp		N/A
	Insulation lacquer not reliable		N/A
	Double-ended high pressure discharge lamp		N/A
	Relevant warning according to 3.2.18 fitted to the luminaire		N/A
5.11 (8.2.2)	Portable luminaire adjusted in most unfavourable position		N/A
5.11 (8.2.3.a)	Class II luminaire:		N/A
	- basic insulated metal parts not accessible during starter or lamp replacement		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	- basic insulation not accessible other than during starter or lamp replacement		N/A
	- glass protective shields not used as supplementary insulation		N/A
5.11 (8.2.3.b)	BC lampholder of metal in class I luminaires shall be earthed		N/A
5.11 (8.2.3.c)	SELV circuits with exposed current carrying parts:		P
	Ordinary luminaire:		P
	- voltage under load (V).....:		P
	- no-load voltage (V).....:		P
	- touch current if applicable (mA)		N/A
	One conductive part insulated if required		N/A
	Other than ordinary luminaire:		N/A
	- nominal voltage (V)		N/A
	Class III luminaire only for connection to SELV		N/A
	Class III luminaire not provided with means for protective earthing		N/A
5.11 (8.2.4)	Portable luminaire have protection independent of supporting surface		N/A
5.11 (8.2.5)	Compliance with the standard test finger or relevant probe		N/A
5.11 (8.2.6)	Covers reliably secured		P
5.11 (8.2.7)	Luminaire other than below with capacitor > 0,5 μ F not exceed 50 V 1 min after disconnection		P
	Portable luminaire with capacitor > 0,1 μ F (0.25) not exceed 34 V 1 s after disconnection		N/A
	Other luminaires with capacitor > 0,1 μ F (0.25) with plug and track adaptors not exceed 60 V 5 s after disconnection		N/A

5.12 (12)	ENDURANCE TEST AND THERMAL TEST	P
	If IP > IP 20 relevant test of (12.4), (12.5), (12.6) and 12.7 after (9.2) before (9.3) specified in 5.13	P
5.12 (12.3)	Endurance test:	P

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	- mounting- position..... :		—
	- test temperature (°C)..... :		—
	- total duration (h)..... :		—
	- supply voltage: Un factor; calculated voltage (V).... :		—
	- lamp used..... :		—
5.12 (12.3.2)	After endurance test:		P
	- no part unserviceable		P
	- luminaire not unsafe		P
	- no damage to track system		N/A
	- marking legible		P
	- no cracks, deformation etc.		P
5.12 (12.4)	Thermal test (normal operation)	(see Annex 2)	N/A
5.12 (12.5)	Thermal test (abnormal operation)	(see Annex 2)	N/A
5.12 (12.6)	Thermal test (failed lamp control gear condition):		N/A
5.12 (12.6.1)	Through wiring or looping-in wiring loaded by a current of (A) :		—
	- case of abnormal conditions..... :		—
	- electronic lamp control gear		N/A
	- measured winding temperature (°C): at 1,1 Un :		—
	- measured mounting surface temperature (°C) at 1,1 Un..... :		N/A
	- calculated mounting surface temperature (°C) :		N/A
	- track- mounted luminaires		N/A
5.12 (12.6.2)	Temperature sensing control		N/A
	- case of abnormal conditions..... :		—
	- thermal link		N/A
	- manual reset cut-out		N/A
	- auto reset cut-out		N/A
	- measured mounting surface temperature (°C)..... :		N/A
	- track- mounted luminaires		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
5.12 (12.7)	Thermal test (failed lamp control gear in plastic luminaires):		N/A
5.12 (12.7.1)	Luminaire without temperature sensing control		N/A
5.12 (12.7.1.1)	Luminaire with fluorescent lamp $\leq 70W$		N/A
	Test method 12.7.1.1 or Annex W		—
	Test according to 12.7.1.1:		N/A
	- case of abnormal conditions.....		—
	- Ballast failure at supply voltage (V)		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
	Test according to Annex W:		N/A
	- case of abnormal conditions.....		—
	- measured winding temperature (°C): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....		—
	- calculated temperature of fixing point/exposed part (°C).....		—
	Ball-pressure test.....	See Table 5.15 (13.2.1)	N/A
5.12 (12.7.1.2)	Luminaire with discharge lamp, fluorescent lamp $> 70W$, transformer $> 10 VA$		N/A
	- case of abnormal conditions.....		—
	- measured winding temperature (°C): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....		—
	- calculated temperature of fixing point/exposed part (°C).....		—
	Ball-pressure test.....	See Table 5.15 (13.2.1)	N/A
5.12 (12.7.1.3)	Luminaire with short circuit proof transformers $\leq 10 VA$		N/A
	- case of abnormal conditions.....		—
	- Components retained in place after the test		N/A
	- Test with standard test finger after the test		N/A
5.12 (12.7.2)	Luminaire with temperature sensing control		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	- thermal link.....:	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- manual reset cut-out.....:	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- auto reset cut-out.....:	Yes <input type="checkbox"/> No <input type="checkbox"/>	—
	- case of abnormal conditions.....:		—
	- highest measured temperature of fixing point/ exposed part (°C):.....:		—
	Ball-pressure test:.....:	See Table 5.15 (13.2.1)	N/A
5.12.1 (-)	Reduction 10 °C of measured temperatures if for outdoor use		—
5.12.2 (-)	Glass covers used within the thermal limits		N/A

5.13 (9)	RESISTANCE TO DUST AND MOISTURE	P
5.13 (-)	If IP > IP 20 the order of tests as specified in clause 5.12	P
5.13 (9.2)	Tests for ingress of dust, solid objects and moisture:	P
	- classification according to IP.....:	IP65
	- mounting position during test.....:	As in normal use
	- fixing screws tightened; torque (Nm).....:	0.8Nm
	- tests according to clauses.....:	—
	- electric strength test afterwards	N/A
	a) no deposit in dust-proof luminaire	P
	b) no talcum in dust-tight luminaire	N/A
	c) no trace of water on current-carrying parts or on insulation where it could become a hazard	N/A
	c.1) For luminaires without drain holes – no water entry	P
	c.2) For luminaires with drain holes – no hazardous water entry	N/A
	d) no water in watertight or pressure watertight luminaire	P
	e) no contact with live parts (IP 2X)	N/A
	e) no entry into enclosure (IP 3X and IP 4X)	N/A
	e) no contact with live parts through drain holes and ventilation slots (IP3X and IP4X)	N/A
	f) no trace of water on part of lamp requiring protection from splashing water	N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	g) no damage of protective shield or glass envelope		N/A
5.13 (9.3)	Humidity test 48 h		P
5.14 (10)	INSULATION RESISTANCE AND ELECTRIC STRENGTH		N/A
5.14 (10.2.1)	Insulation resistance test		P
	Cable or cord covered by metal foil or replaced by a metal rod of mm Ø		N/A
	Insulation resistance (MΩ).....		N/A
	SELV		P
	- between current-carrying parts of different polarity:		N/A
	- between current-carrying parts and mounting surface.....		P
	- between current-carrying parts and metal parts of the luminaire.....		P
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts.....		N/A
	- Insulation bushings as described in Section 5		N/A
	Other than SELV		N/A
	- between live parts of different polarity.....		N/A
	- between live parts and mounting surface.....		N/A
	- between live parts and metal parts.....		N/A
	- between live parts of different polarity through action of a switch.....		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts.....		N/A
	- Insulation bushings as described in Section 5		P
5.14 (10.2.2)	Electric strength test		P
	Dummy lamp		N/A
	Luminaires with ignitors after 24 h test		N/A
	Luminaires with manual ignitors		N/A
	Test voltage (V).....		P
	SELV		P

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
	- between current-carrying parts of different polarity:		N/A
	- between current-carrying parts and mounting surface.....:		P
	- between current-carrying parts and metal parts of the luminaire.....:		P
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts.....:		N/A
	- Insulation bushings as described in Section 5		N/A
	Other than SELV		N/A
	- between live parts of different polarity.....:		N/A
	- between live parts and mounting surface.....:		N/A
	- between live parts and metal parts.....:		N/A
	- between live parts of different polarity through action of a switch.....:		N/A
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts.....:		N/A
	- Insulation bushings as described in Section 5		P
5.14 (10.3)	Touch current or protective conductor current (mA):		P

5.15 (13)	RESISTANCE TO HEAT, FIRE AND TRACKING		N/A
5.15 (13.2.1)	Ball-pressure test.....:	See Test Table 5.15 (13.2.1)	N/A
5.15 (13.3.1)	Needle-flame test (10 s).....:	See Test Table 5.15 (13.3.1)	N/A
5.15 (13.3.2)	Glow- wire test (650°C).....:	See Test Table 5.15 (13.3.2)	N/A
5.15 (13.4)	Proof tracking test (IEC 60112).....:	See Test Table 5.15 (13.4)	N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict

5.7 (11.2)	TABLE: Creepage distances and clearances							P
	Minimum distances (mm) for a.c. (50/60 Hz) sinusoidal voltages							P
	Applicable part of IEC 60598-1 Table 11.1* and 11.2*							P
	Insulation type **	Measured clearance	Required		Measured creepage	Required		
			clearance	*Table		creepage	*Table	
Distance 1:	B	2,5	1,5	11.1.B	2,5	2,5	Table 11.1.A	
Working voltage (V)..... :					6.4V~		—	
PTI..... :					<div>< 600 <input checked="" type="checkbox"/></div> <div><input type="checkbox"/></div> <div>≥ 600</div>		—	
Pulse voltage if applicable (kV)							—	
Supplementary information:								
Distance 2:	R	5,0	3,0	11.1.B	5,0	5,0	Table 11.1.A	
Working voltage (V)..... :							—	
PTI..... :					<div>< 600 <input checked="" type="checkbox"/></div> <div><input type="checkbox"/></div> <div>≥ 600</div>		—	
Pulse voltage if applicable (kV)							—	
Supplementary information:								
Distance 3:								
Working voltage (V)..... :							—	
PTI..... :					<div>< 600 <input type="checkbox"/></div> <div><input type="checkbox"/></div> <div>≥ 600</div>		—	
Pulse voltage if applicable (kV)							—	
Supplementary information:								

** Insulation type: B – Basic; S – Supplementary; R – Reinforced. See also IEC 60598-1 Annex M.

5.15 (13.2.1)	TABLE: Ball Pressure Test of Thermoplastics				N/A
Allowed impression diameter (mm):					—
Object/ Part No./ Material		Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)	

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict

Supplementary information:

5.15 (13.3.1)	TABLE: Needle-flame test (IEC 60695-11-5)				N/A
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
Supplementary information:					

5.15 (13.3.2)	TABLE: Glow-wire test (IEC 60695-2-11)				N/A
Glow wire temperature		650°C			—
Object/ Part No./ Material	Manufacturer/ trademark	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict	
Any flame or glowing of the sample extinguished within 30 s of withdrawing the glow-wire, and any burning or molten drop did not ignite the underlying parts (Yes/No).....:					
Supplementary information:					

5.15 (13.4)	TABLE: Proof tracking test (IEC 60112)				N/A
Test voltage PTI		175 V			—
Object/ Part No./ Material	Manufacturer/ trademark	Withstand 50 drops without failure on three places or on three specimens			Verdict
Supplementary information:					

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict

ANNEX 1		List of critical components and materials		
Component	manufacturers / trademark	Type / model	Value / rating	Approval/ Reference
Power supply cord	Various	2464	VW-1, 105°C, 22AWG	VDE
LED PCB	Heshan Dongli Electronic Technologies Co Ltd	EPA-M2	V-0, 130°C	UL and Test with appliance

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict

	ANNEX 2: temperature measurements, thermal tests of Section 12				P		
	Type reference..... :		SOLAR LED STREETLIGHT			—	
	Lamp used.....:		lamp			—	
	Ballast used.....:		—			—	
	Mounting position of luminaire..... :		As in normal use			—	
	Supply wattage (W)..... :		100W			—	
	Supply current (A)..... :		-			—	
	Table: measured temperatures corrected for Ta = 25°C:					P	
	- abnormal operating mode..... :		—			—	
	- test 1: rated voltage.....:		6.4V			—	
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage..... :		—			—	
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage.....:		—			—	
	- test 4: 1,1 times rated voltage or 1,05 times rated wattage..... :		—			—	
temperature (C) of part		clause 12.4 - normal				clause 12.5 - abnormal	
		test 1	test 2	test 3	limits	test 4	limit
Metal enclosure		--	52.2	--	90	--	--
Internal wire		--	68.8	--	105	--	--
LED body		--	102.3	--	Ref	--	--
Diffuser		--	83.4	--	125	--	--
Mounting surface		--	35.0	--	90	--	--
Lighting surface (10cm)		--	32.1	--	90	--	--
Ambient:		--	25.0	--	--	--	--

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict

	ANNEX 3: SCREW TERMINALS (PART OF THE LUMINAIRE)		N/A
(14)	SCREW TERMINALS		N/A
(14.2)	Type of terminal:		—
	Rated current (A):		—
(14.3.2.1)	One or more conductors		N/A
(14.3.2.2)	Special preparation		N/A
(14.3.2.3)	Terminal size		N/A
	Cross-sectional area (mm ²):		N/A
(14.3.3)	Conductor space (mm):		N/A
(14.4)	Mechanical tests		N/A
(14.4.1)	Minimum distance		N/A
(14.4.2)	Cannot slip out		N/A
(14.4.3)	Special preparation		N/A
(14.4.4)	Nominal diameter of thread (metric ISO thread):		N/A
	External wiring		N/A
	No soft metal		N/A
(14.4.5)	Corrosion		N/A
(14.4.6)	Nominal diameter of thread (mm):		N/A
	Torque (Nm):		N/A
(14.4.7)	Between metal surfaces		N/A
	Lug terminal		N/A
	Mantle terminal		N/A
	Pull test; pull (N):		N/A
(14.4.8)	Without undue damage		N/A
	ANNEX 4: SCREWLESS TERMINALS (PART OF THE LUMINAIRE)		N/A
(15)	SCREWLESS TERMINALS		N/A
(15.2)	Type of terminal..... :		—
	Rated current (A)..... :		—
(15.3.1)	Material		N/A
(15.3.2)	Clamping		N/A
(15.3.3)	Stop		N/A
(15.3.4)	Unprepared conductors		N/A
(15.3.5)	Pressure on insulating material		N/A

EN 60598-1 & EN 60598-2-5			
Clause	Requirement – Test	Result - Remark	Verdict
(15.3.6)	Clear connection method		N/A
(15.3.7)	Clamping independently		N/A
(15.3.8)	Fixed in position		N/A
(15.3.10)	Conductor size		N/A
	Type of conductor		N/A
(15.5.1)	Terminals internal wiring		N/A
(15.5.1.1)	Pull test spring-type terminals (4 N, 4 samples)		N/A
(15.5.1.2)	Pull test pin or tab terminals (4 N, 4 samples)		N/A
	Insertion force not exceeding 50 N		N/A
(15.5.2)	Permanent connections: pull-off test (20 N)		N/A
(15.6)	Electrical tests		N/A
	Voltage drop (mV) after 1 h (4 samples).....:		N/A
	Voltage drop of two inseparable joints		N/A
	Number of cycles.....:		—
	Voltage drop (mV) after 10th alt. 25th cycle (4 samples).....:		N/A
	Voltage drop (mV) after 50th alt. 100th cycle (4 samples).....:		N/A
	After ageing, voltage drop (mV) after 10th alt. 25th cycle (4 samples).....:		N/A
	After ageing, voltage drop (mV) after 50th alt. 100th cycle (4 samples).....:		N/A
(15.7)	Terminals external wiring		N/A
	Terminal size and rating		N/A
(15.8.1)	Pull test spring-type terminals (4 samples); pull (N)		N/A
	Pull test pin or tab terminals (4 samples); pull (N)		N/A
(15.9)	Contact resistance test		N/A
	Voltage drop (mV) after 1 h		N/A

Appendix 1

Photo documentation



Photo 3

View:

- ☐ Front
- ☐ Rear
- ☐ Right side
- ☐ Left side
- ☐ Top
- ☐ Bottom
- ☒ Internal



Photo 4

View:

- ☐ Front
- ☐ Rear
- ☐ Right side
- ☐ Left side
- ☐ Top
- ☐ Bottom
- ☒ Internal





Photo 5

View:

- ☐ Front
- ☐ Rear
- ☐ Right side
- ☐ Left side
- ☐ Top
- ☐ Bottom
- ☒ Internal



--END.--